

MICHAEL AAF (KDPPG)

MISSED APPROACH: Climb to 4760 then climbing right turn to 8500 direct ETUBY and hold, continue climb in hold to 8500.

CTAF

126.2 270.3

† CAUTION: Missed Approach
Minimum Climb Rate to 6000

Knots	60	120	180	240	300	360
V/V(fpm)	337	674	1011	1348	1685	2022

8500 

Procedure NA for arrivals on DTA VORTAC
airways radials R-348 CW R-008.

R-6406A




R-6407

MSA HISUK 25 NM
12,200

R-6402A

VGSI and descent angles
not coincident

VDP NA with Wendover
altimeter setting minimums.

4760	8500	ETUBY
		

8500
3.00°
TCH 55

ETUBY

UWOZO

ELEV	4351	TDZE	4346
------	------	------	------

122° from FAF
Rwy 12 ldg 10,000'
Rwy 30 ldg 9998'

CATEGORY	A	B	C	D	E
LNAY MDA	4640-1 294 (300-1)		5140-2 794 (800-2½)		
C CIRCLING	4800-1 449 (500-1)	4920-1 569 (600-1)	5160-2½ 809 (900-2½)	5880-3 1529 (1600-3)	NA
† BELOW MINIMA REQUIRES MISSED APPROACH CLIMB GRADIENT OF 337 ft/NM					
LNAY MDA	NA		4640-1 294 (300-1)		
* WENDOVER ALTIMETER SETTING - MINIMUMS					
LNAY MDA	4800-1 454 (500-1)		5300-3 954 (1000-3)		
C CIRCLING	4960-1 609 (700-1)	5080-1 729 (800-1)	5320-3 969 (1000-3)	6040-3 1689 (1700-3)	NA
† BELOW MINIMA REQUIRES MISSED APPROACH CLIMB GRADIENT OF 337 ft/NM					
LNAY MDA	NA		4800-3 454 (500-3)		

MICHAEL AAF (KDPPG)

Amdt 2 30MAR17

RNAV (GPS) RWY 12

SW-4, 31 DEC 2020 to 28 JAN 2021

SW-4, 31 DEC 2020 to 28 JAN 2021