


TAKEOFF MINIMUMS

Rwy 3: Standard with minimum climb of 445′ per NM to 4600.
Rwy 21: Standard with minimum climb of 300′ per NM to 4600.

NOTE: RNAV 1.
NOTE: Turbojets and turboprops only.
NOTE: RADAR required.
NOTE: GPS required.
NOTE: JARPA TRANSITION ATC assigned only.
NOTE: YOOPR TRANSITION ATC assigned only.
NOTE: CARTL TRANSITION for FLG or PGA terminal arrivals only.
NOTE: Aircraft departing KGEU and KGYR ATC assigned only.
NOTE: Rwy 21: Do not exceed 210K until established on assigned heading.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 3: Climbing left turn heading 335° or as assigned by ATC, thence. . . .

TAKEOFF RUNWAY 21: Climbing right turn heading 335° or as assigned by ATC. Thence. . . .

. . . .expect RADAR vectors to QUAKY, then on track 343° to SNOBL, then on (transition). Maintain ATC assigned altitude, expect filed altitude 3 minutes after departure.

CARTL TRANSITION (SNOBL6.CARTL)

GRAND CANYON TRANSITION (SNOBL6.GCN)

JARPA TRANSITION (SNOBL6.JARPA)

RIMMM TRANSITION (SNOBL6.RIMMM)

YOOPR TRANSITION (SNOBL6.YOOPR)

NOTE: Chart not to scale.



SW-4, 31 DEC 2020 to 28 JAN 2021